

Techno Plast L

Lime replacer in plastering bricklaying mortar

Description

Techno Plast L is an admixture to sand-cement mortar mixes to improve workability and replaces lime in plastering and bricklaying mortars. Is based on polymerized resins and is free from calcium chloride and similar salts

Advantages

- Entrains a controlled amount of microscopic air bubbles which act as frictionless aggregate in the mortar and reduces the water requirement for a given consistency
- Permits saving in cement content and minimize the risk of cracking and crazing of plastering
- Improves moisture retention and bond properties of the mortar and minimizes the risk of separation of plastering from wall surface
- Produces mortars highly resistant to disruption caused by ground moisture capillary action
- Eliminates use of lime, saving storage space and plastering failures due to unsound lime
- Highly economical, saves 10-20 of cement

Instructions for use

Techno Plast L is a light brown liquid to be added directly to the mortar mix or where more convenient, may be premixed with the water

Normal rate of addition is about 0.2 kg. Of Techno Mix Wp per bag of cement or about 1 kg

Per 200 liters of water

Storage

months under suitable storage conditions 18

packages

kg, 5 kg, 25 kg 1

Modern Technologies for Construction Chemicals

Factory: Wadi Elnatroun – First Industrial Area.
Head Office: New Maadi – 3\288 St. from Aljazeera St.
Fax. & Tel.: 02-25200833 Mob. : 010 209 65554
www.mtcchem.com